Certificate No.: LS250046GCC-0

Date of issue: 2025-05-09 Valid until: Indefinitely

Applicant: Wuxi Solinteg Power Co., Ltd.

Building H1-1001, No. 6 Jingxian Road, Xinwu District, 214135 Wuxi, Jiangsu

Province, China

Product: Hybrid Inverter

Model(s): M2HT-25K-150, M2HT-29.9K-150, M2HT-30K-150 , M2HT-40K-150, M2HT-50K-150

Trademark: SOLINTEG

Technical data: Nominal active output power [kW]: 25 ~ 50

Nominal output AC voltage [V]: 230V /400 V (3L + N + PE, 50 / 60 Hz)

(For further details see A.2 on p.2)

Software version: V1.00

Applied standard(s) / IEC 60068-2-1:2007

guideline(s): Environmental testing - Part 2-1: Tests – Test A: Cold

IEC 60068-2-2:2007

Environmental testing - Part 2-2: Tests - Test B: Dry heat

IEC 60068-2-14:2023

Environmental testing - Part 2-14: Tests - Test N: Change of temperature

IEC 60068-2-30:2005

Environmental testing - Part 2-30: Tests – Test Db and guidance: Damp heat, cyclic (12 + 12-

hour cycle)

IEC 60068-2-64:2008

Environmental testing - Part 2-64: Tests - Test Fh: Vibration, broadband random and guidance

IEC 61683:1999, EN 61683:2000

Photovoltaic systems - Power conditioners - Procedure for measuring efficiency

IEC 61727:2004

Photovoltaic (PV) systems - Characteristics of the utility interface

IEC 62116:2014, EN 62116:2014

Utility-interconnected photovoltaic inverters - Test procedure of islanding prevention measures

Certification scheme: CMPD-01

Test report no.: HC2412270309GC01 (2025-04-27)

HC2412270309GC02 (2025-04-27) HC2412270309GC03 (2025-04-27) VTL25.01.040E (2025-02-26)

This certificate confirms that the above-mentioned generating unit(s) with corresponding software meet the requirements of the referenced standard(s) / guideline(s) at the time of issuance of the certificate.

This certificate relates to type testing and does not imply LYNS's endorsement, approval, certification or on-going control of the product(s), either in terms of performance, design, manufacture or materials used. This certificate and the results stated herein relate solely to the sample product(s) tested and to the specific tests undertaken.

The certificate will remain valid for the stated period providing no changes are made to the product, production method etc. This certificate is only valid when this is also found at http://www.lyns-tci.com/en/certificate-search or contact Lyns-tci Technology Guangdong Co., Ltd..

This certificate is for the exclusive use of LYNS's Client and is provided pursuant to the agreement between LYNS and its Client. LYNS's responsibility and liability are limited to the terms and conditions of the agreement. LYNS assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned using this verification.

The certificate is comprised of 2 pages (including Annex of 1 pages).

Dongguan, 2025-05-09

Dipl.-Ing. Weizhao Zheng Head of certification body

Certification body Lyns-tci Technology Guangdong Co., Ltd. accredited according to ISO/IEC 17065 for product certification.

This document shall not be reproduced, except in full, without the written approval of Lyns-tci Technology Guangdong Co., Ltd.



Annex to the Certificate No.: LS250046GCC-0

A.1 Revision history of the certificate

Rev. No.	Date	Changes	Status
Rev. 0	2025-05-09	Initial issue	Active

A.2 Technical data of the power generating unit(s)

Model	M2HT-25K- 150	M2HT- 29.9K-150	M2HT-30K- 150	M2HT-40K- 150	M2HT-50K- 150
Input PV (DC)					
Max. DC input voltage [V]			1000		
Operating MPPT voltage range [V]			200 ~ 950		
Max. input DC current [A]			40 A * 4		
Input Battery					
Battery voltage range (V)			150-840	15 11 120 STATE	
Max. charging/discharge current (A)			150		- Transmitte
Output (AC)					
Rated output AC voltage [V]		230V / 400	V(3L + N + PE,	50 / 60 Hz)	
Max. Output AC current [A]	37.9	45.3	45.5	60.6	75.8
Rated active power [kW]	25	29.9	30	40	50
Max. apparent power [kVA]	25	29.9	30	40	50
Operating temperature range			-30°C ~ +60°C		
Degree of protection		IP66 (according to EN 60529)			
Protection class		I (according to IEC 62109-1)			
Over voltage category		AC: III; DC: II (according to IEC 62109-1)			
Topology		No galvanic isolation			
Software version		V1.00			
Manufacturing factory		Power Co., Lt ang 1st Road, X	d. (inwu District, W	′uxi, Jiangsu Pro	ovince, China

A.3 Remarks for type testing

Testing laboratory	Lyns-tci Technology Guangdong Co., Ltd. Room 1201, Unit 2, Building 18, No. 7, Science and Technology Boulevard, Houjie Town, Dongguan City, Guangdong, 523960 P.R.C (Accredited acc. ISO/IEC 17025: A2LA Accreditation no. 5200.02)
Testing location	Same as above
Measurement period	2025-01-02 ~ 2025-04-17

Testing laboratory	Jiangsu Vehicle Testing Services Co., Ltd.	
	Building 6, No.278, Huajin Road, Tongan, SND, Suzhou, Jiangsu, China	
	(Accredited acc. ISO/IEC 17025: CNAS Accreditation no. L12681)	
Testing location	Same as above	
Measurement period	2025-01-17 ~ 2025-01-22	